Application No.: 10/518,212 Docket No. PU020291
Art Unit: 2616 Customer No. 24498

Listing and Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application.

Cancel claims 1-18

Add claims 19-24

19. (new) An expandable router for routing a signal from at least one input to one or more outputs, comprising:

at least X routing components, where X is an integer greater than two, each of the X routing components having first and second routing engines, each routing engine having M inputs and N outputs where M and N are integers both greater than one, each routing engine routing a signal from one of the M inputs to one or more of the N outputs.

each first routing engine of each of the X routing components having its inputs coupled by links to inputs of others of the first routing engines of the X routing components;

each second routing engine of each of the X routing components having its inputs coupled by links to inputs of others of the second routing engines of the X routing components;

wherein the coupling of the inputs of the inputs of the routing engines affords the routing engines with a common set of XM inputs, with each of the first and second routing engines in each routing component serving as a backup to the other of the routing engines in the same routing component.

20. (new) The router according to claim 19 wherein the links between inputs of each routing engine of a routing component and inputs of a routing engine of another routing component are bi-directional.

-2-

Application No.: 10/518,212 Docket No. PU020291
Art Unit: 2616 Customer No. 24498

21. (new) The router according to claim 19 wherein the links between inputs of each routing engine of a routing component and inputs of a routing engine of another routing component comprise pairs of unidirectional links.

- 22. (new) The router according to claim 19 wherein each routing component further comprises first and second expansion modules.
- 23. (new) The router according to claim 22 wherein each expansion module comprises first and second memories each capable of storing data received at the expansion module.
- 24. (new) The method according to claim 23 wherein each expansion module further includes a controller for transferring data between the first and second memories.

-3-